

Long-Type



Product Description

- Certificated Protection: Ex d II Gb X (Applicable Location: IIA, IIB, IIC)
- Material: Stainless Steel
- Operation temperature: -20°C ~ + 40 °C
- Thread Standards:
ISO – I EC / EN 60423, IEC/EN 50262
PF – JIS B 0202
NPT – ANSI B2.1


Part Number	Entry Thread Size "A"	Thread Length "B"	Cable Acceptance "E"		Gland Length "F" (less entry)	Across Flats "G"	Hexagon Dimensions "K"
			Max	Min			
Without Socket Set Screw / With Socket Set Screw							
THT-2GM020UXd*0807	M20	19.7mm	8.0mm	7.0mm	66.7mm	23.0 mm	32 / 40mm
THT-2GM020UXd*1009	M20	19.7mm	10.0mm	9.0mm	66.7mm	23.0 mm	32 / 40mm
THT-2GM020UXd*1211	M20	19.7mm	12.0mm	11.0mm	66.7mm	23.0 mm	32 / 40mm
THT-2GG012UXd*0807	G1/2"	19.7mm	8.0mm	7.0mm	66.7mm	23.0 mm	32 / 40mm
THT-2GG012UXd*1009	G1/2"	19.7mm	10.0mm	9.0mm	66.7mm	23.0 mm	32 / 40mm
THT-2GG012UXd*1211	G1/2"	19.7mm	12.0mm	11.0mm	66.7mm	23.0 mm	32 / 40mm
THT-2GN034UXd*0605	NPT3/4"	18.0mm	6.0mm	5.0mm	67.3mm	28.5 mm	38 / 46mm
THT-2GN034UXd*0807	NPT3/4"	18.0mm	8.0mm	7.0mm	67.3mm	28.5 mm	38 / 46mm
THT-2GN034UXd*8575	NPT3/4"	18.0mm	8.5mm	7.5mm	67.3mm	28.5 mm	38 / 46mm
THT-2GN034UXd*0908	NPT3/4"	18.0mm	9.0mm	8.0mm	67.3mm	28.5 mm	38 / 46mm
THT-2GN034UXd*1009	NPT3/4"	18.0mm	10.0mm	9.0mm	67.3mm	28.5 mm	38 / 46mm
THT-2GN034UXd*1211	NPT3/4"	18.0mm	12.0mm	11.0mm	67.3mm	28.5 mm	38 / 46mm
THT-2GN034UXd*1413	NPT3/4"	18.0mm	14.0mm	13.0mm	67.3mm	28.5 mm	38 / 46mm
THT-2GN034UXd*1615	NPT3/4"	18.0mm	16.0mm	15.0mm	67.3mm	28.5 mm	38 / 46mm
THT-2GN012UXd*0807	NPT 1/2"	18.0mm	8.0mm	7.0mm	66.7mm	23.0 mm	32 / 40mm
THT-2GN012UXd*1009	NPT 1/2"	18.0mm	10.0mm	9.0mm	66.7mm	23.0 mm	32 / 40mm
THT-2GN012UXd*1211	NPT 1/2"	18.0mm	12.0mm	11.0mm	66.7mm	23.0 mm	32 / 40mm

* — A: With Socket Set Screw
B: Without Socket Set Screw


Sleeve and connector are available upon request.

Without Connector

▼ Without Socket Set Screw



▼ With Socket Set Screw



Part Number	Entry Thread Size "A"	Thread Length "B"	Cable Acceptance "E"		Gland Length "F" (less entry)	Across Flats "G"	Hexagon Dimensions "K"
			Max	Min			
Without Socket Set Screw / With Socket Set Screw							
THT-2GG034UXd*0605	G3/4"	19.5mm	6.0mm	5.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GG034UXd*0807	G3/4"	19.5mm	8.0mm	7.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GG034UXd*8575	G3/4"	19.5mm	8.5mm	7.5mm	67.3mm	28.5mm	38 / 46mm
THT-2GG034UXd*0908	G3/4"	19.5mm	9.0mm	8.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GG034UXd*1009	G3/4"	19.5mm	10.0mm	9.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GG034UXd*1211	G3/4"	19.5mm	12.0mm	11.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GG034UXd*1413	G3/4"	19.5mm	14.0mm	13.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GG034UXd*1615	G3/4"	19.5mm	16.0mm	15.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GM025UXd*0605	M25	19.5mm	6.0mm	5.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GM025UXd*0807	M25	19.5mm	8.0mm	7.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GM025UXd*8575	M25	19.5mm	8.5mm	7.5mm	67.3mm	28.5mm	38 / 46mm
THT-2GM025UXd*0908	M25	19.5mm	9.0mm	8.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GM025UXd*1009	M25	19.5mm	10.0mm	9.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GM025UXd*1211	M25	19.5mm	12.0mm	11.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GM025UXd*1413	M25	19.5mm	14.0mm	13.0mm	67.3mm	28.5mm	38 / 46mm
THT-2GM025UXd*1615	M25	19.5mm	16.0mm	15mm	67.3mm	28.5mm	38 / 46mm

* — A: With Socket Set Screw
B: Without Socket Set Screw

Sleeve and connector are available upon request.